

Errata

“Pulse Control LSI PCL6025B User’s Manual” (DA70119-1/1E) contains the error described below.

Please confirm the following corrections.

Page	Corrected part	Incorrect	Correct																																																																					
4	1-2. Features ◆ Servomotor I/F The ERC signal is a pulsed output. The pulse length can be set.	(12 μs to 104 ms. A level output is also available.)	(11 μs to 100 ms. A level output is also available.)																																																																					
7	4. Functions of Terminals <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Signal name</th> <th style="text-align: center;">Terminal No.</th> <th style="text-align: center;">Input/ output</th> </tr> </thead> <tbody> <tr> <td>IF0</td> <td style="text-align: center;">3,</td> <td></td> </tr> <tr> <td>IF1</td> <td style="text-align: center;">4</td> <td></td> </tr> </tbody> </table>	Signal name	Terminal No.	Input/ output	IF0	3,		IF1	4		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Input/ output</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Input</td> </tr> </tbody> </table>	Input/ output	Input	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Input/ output</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Input U</td> </tr> </tbody> </table>	Input/ output	Input U																																																								
Signal name	Terminal No.	Input/ output																																																																						
IF0	3,																																																																							
IF1	4																																																																							
Input/ output																																																																								
Input																																																																								
Input/ output																																																																								
Input U																																																																								
		Supplement) CPU interface setting terminal pins, IF0 and IF1, are pulled up internally. When driving with open collectors, pull up using 5 to 10 kΩ resistors externally.																																																																						
10 11	4. Functions of Terminals <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Signal name</th> <th style="text-align: center;">Terminal No.</th> <th style="text-align: center;">Input/ output</th> </tr> </thead> <tbody> <tr> <td>P0x/FUPx</td> <td style="text-align: center;">71</td> <td></td> </tr> <tr> <td>P0y/FUPy</td> <td style="text-align: center;">110</td> <td></td> </tr> <tr> <td>P1x/FDWx</td> <td style="text-align: center;">72</td> <td></td> </tr> <tr> <td>P1y/FDWy</td> <td style="text-align: center;">111</td> <td></td> </tr> <tr> <td>P2x/MVCx</td> <td style="text-align: center;">73</td> <td></td> </tr> <tr> <td>P2y/MVCy</td> <td style="text-align: center;">112</td> <td></td> </tr> <tr> <td>P3x/CP1x (+SLx)</td> <td style="text-align: center;">74</td> <td></td> </tr> <tr> <td>P3y/CP1y (+SLy)</td> <td style="text-align: center;">113</td> <td></td> </tr> <tr> <td>P4x/CP2x (-SLx)</td> <td style="text-align: center;">75</td> <td></td> </tr> <tr> <td>P4y/CP2y (-SLy)</td> <td style="text-align: center;">114</td> <td></td> </tr> <tr> <td>P5x/CP3x</td> <td style="text-align: center;">76</td> <td></td> </tr> <tr> <td>P5y/CP3y</td> <td style="text-align: center;">115</td> <td></td> </tr> <tr> <td>P6x/CP4x</td> <td style="text-align: center;">77</td> <td></td> </tr> <tr> <td>P6y/CP4y</td> <td style="text-align: center;">116</td> <td></td> </tr> <tr> <td>P7x/CP5x</td> <td style="text-align: center;">78</td> <td></td> </tr> <tr> <td>P7y/CP5y</td> <td style="text-align: center;">117</td> <td></td> </tr> </tbody> </table>	Signal name	Terminal No.	Input/ output	P0x/FUPx	71		P0y/FUPy	110		P1x/FDWx	72		P1y/FDWy	111		P2x/MVCx	73		P2y/MVCy	112		P3x/CP1x (+SLx)	74		P3y/CP1y (+SLy)	113		P4x/CP2x (-SLx)	75		P4y/CP2y (-SLy)	114		P5x/CP3x	76		P5y/CP3y	115		P6x/CP4x	77		P6y/CP4y	116		P7x/CP5x	78		P7y/CP5y	117		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Input/ output</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> <tr> <td style="text-align: center;">Input/ Output*</td> </tr> </tbody> </table>	Input/ output	Input/ Output*	Input/ Output*	Input/ Output*	Input/ Output*	Input/ Output*	Input/ Output*	Input/ Output*	Input/ Output*	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Input/ output</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> <tr> <td style="text-align: center;">Input/ output</td> </tr> </tbody> </table>	Input/ output	Input/ output	Input/ output	Input/ output	Input/ output	Input/ output	Input/ output	Input/ output	Input/ output
Signal name	Terminal No.	Input/ output																																																																						
P0x/FUPx	71																																																																							
P0y/FUPy	110																																																																							
P1x/FDWx	72																																																																							
P1y/FDWy	111																																																																							
P2x/MVCx	73																																																																							
P2y/MVCy	112																																																																							
P3x/CP1x (+SLx)	74																																																																							
P3y/CP1y (+SLy)	113																																																																							
P4x/CP2x (-SLx)	75																																																																							
P4y/CP2y (-SLy)	114																																																																							
P5x/CP3x	76																																																																							
P5y/CP3y	115																																																																							
P6x/CP4x	77																																																																							
P6y/CP4y	116																																																																							
P7x/CP5x	78																																																																							
P7y/CP5y	117																																																																							
Input/ output																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ Output*																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
Input/ output																																																																								
		Supplement) General-purpose input/output terminal pins, P0 to P7, are NOT pulled up internally. Be sure to pull up using 5 to 10 kΩ resistors externally.																																																																						

Page	Corrected part	Incorrect	Correct			
36	8-3-13. RENV1 register <table border="1"> <tr> <td>12 to 14</td> <td>EPW0 to 2</td> <td>Specify the pulse width of the ERC output signal.</td> </tr> </table>	12 to 14	EPW0 to 2	Specify the pulse width of the ERC output signal.	000 : 12 μ s 001 : 102 μ s 010 : 409 μ s 011 : 1.6 ms 100 : 13 ms 101 : 52 ms 110 : 104 ms 111 : Level output	000 : 11 to 13 μ s 001 : 91 to 98 μ s 010 : 364 to 391 μ s 011 : 1.4 to 1.6 ms 100 : 11 to 13 ms 101 : 46 to 50 ms 110 : 93 to 100 ms 111 : Level output
12 to 14	EPW0 to 2	Specify the pulse width of the ERC output signal.				
36	8-3-13. RENV1 register <table border="1"> <tr> <td>16 to 17</td> <td>ETW0 to 1</td> <td>Specify the ERC signal OFF timer time.</td> </tr> </table>	16 to 17	ETW0 to 1	Specify the ERC signal OFF timer time.	00 : 0 μ s 01 : 12 μ s 10 : 1.6 ms 11 : 104 ms	00 : 0 μ s 01 : 11 to 13 μ s 10 : 1.4 to 1.6 ms 11 : 93 to 100 ms
16 to 17	ETW0 to 1	Specify the ERC signal OFF timer time.				
106	11-6-2. ERC signal <table border="1"> <tr> <td>Set the ERC signal output width</td> </tr> </table>	Set the ERC signal output width	000 : 12 μ s 001 : 102 μ s 010 : 409 μ s 011 : 1.6 ms 100 : 13 ms 101 : 52 ms 110 : 104 ms 111 : Logic level output	000 : 11 to 13 μ s 001 : 91 to 98 μ s 010 : 364 to 391 μ s 011 : 1.4 to 1.6 ms 100 : 11 to 13 ms 101 : 46 to 50 ms 110 : 93 to 100 ms 111 : Level output		
Set the ERC signal output width						
106	11-6-2. ERC signal <table border="1"> <tr> <td>Specify the ERC signal OFF timer time</td> </tr> </table>	Specify the ERC signal OFF timer time	00 : 0 μ s 01 : 12 μ s 10 : 1.6 ms 11 : 104 ms	00 : 0 μ s 01 : 11 to 13 μ s 10 : 1.4 to 1.6 ms 11 : 93 to 100 ms		
Specify the ERC signal OFF timer time						

- End of document -